

Versa Lift 25/35 Features	
Engine:	GM 3.0L
Transmission:	Rexroth Hydrostatic
Drive Axle:	Rockwell Planetary Drive
Tires:	Front 28X16 Poly Rear 22X8 Poly
Grade:	Empty 38% Loaded 17%
Tilt:	Forward 11° Back 6°
Weight:	Gross: 30,000 lbs Boom: 3,000 lbs Forks: 1,500 lbs
Boom Reach:	22' (to center of pin)
Load Capacity:	25,000 lbs @ 24" retracted 35,000 lbs @ 24" extended
Width:	58"
Wheelbase:	76" retracted 112" extended
Additional Features:	
<ul style="list-style-type: none"> - Boom removes in minutes with special Boom stand - Horizontal Boom retracts while using forks - 2-stage direct roller mast 	

Slab Weight (lbs)
1900

Number of Slabs
3

Standard Wheel Base (in)
76

Lifting Capacity w/ Forks Only (lbs)				
Load Center From Fork Face (in)	Counterweight Extension (in)			
	0	12	24	36
	24	24300	28200	32000
36	19400	22500	25500	28600
48	16200	18700	21300	23800
60	13800	16000	18200	20400
72	12100	14000	15900	17800
84	10700	12400	14100	15800

www.a1lift.net

Lifting Capacity w/ Boom Only (lbs)				
Load Center From Boom Face (in)	Counterweight Extension (in)			
	0	12	24	36
	12	23500	27400	31200
24	18800	21900	24900	28000
36	15600	18200	20700	23300
48	13400	15600	17800	19900
60	11700	13600	15500	17400
72	10400	12100	13800	15500
84	9400	10900	12400	13900
96	8500	9900	11300	12700

www.a1lift.net

Lifting Capacity w/ Forks & Boom (lbs)				
Load Center From Boom Face (in)	Counterweight Extension (in)			
	0	12	24	36
	24	17800	20900	24000
36	14800	17400	19900	22500
48	12700	14900	17100	19300
60	11100	13000	14900	16800
72	9900	11600	13300	15000
84	8900	10400	11900	13500
96	8100	9500	10800	12200

www.a1lift.net

***All Load Capacities are rated with the mast vertical.

